



fibersect.multi benefits

SIMPLE

zero training required

one button operation

- none of the complicated monitors or tools required of laser or hand cleaving

increased safety for user

- protects user from stray fibers or other harmful exposures

easy maintenance

- waste bin collects scraps for easy clean-up

palm size portability

battery powered

automate production and reduce human variables

simplifies process

- no more hand scribing
- no more denubbing
- no more air polishing

PRECISE

cuts flat

cuts close to ferrule

consistent, repeatable cuts

superior end face geometry

no heat exposure

ADJUSTABLE

cuts all single and multiple fiber ferrules

- easy change adapter plates enable use with any ferrule or connector
- MTO (4-72 fibers), LC, LC-APC, LC-Duplex, SC, SC-APC, SMA + others

cuts parallel to ferrule face - 0° or 8° (APC)

- compatible with pre-angled ferrules

adjustable cut length

- easily adjusts to cut from 0-600 um from face of ferrule

customizable options

- vacuum dust collector
- foot switch
- cut counter

AFFORDABLE

fraction of the cost of the laser

- allows for process automation that is not cost prohibitive
- allows for multiple units for multiple production lines

savings in production

- increased throughput
- rework costs go down, yield goes up
- high first pass yield
- reduced polishing and manpower
- minimize wasted cable length